


CMI[™] 300 PULSE

ADVANCED YET SIMPLE

The Car-O-Liner **CMI300 Pulse** is the welding machine for repairing cars and building up car bodies in professional workshops.

It is designed to meet the automobile manufacturer's standards for joining processes in thin high-tensile steel, aluminum and stainless steel.

READY FOR AUTO BUSINESS



COMPACT AND FULLY DIGITAL WELDING MACHINE

EASY SWITCH-OVER WITH DUO OR TRIO

The **CMI300 Pulse** is available in three versions: SINGLE, DUO and TRIO. The DUO version has room for two 15kg wire coils and the TRIO version for three 5kg wire coils, providing easy switch-over between operations without change of hose, wire, wire drive rolls and gas. The machine will automatically establish which torch/wire feed unit is active.

MIG BRAZING

In addition to sheet metal welding, the **CMI300 Pulse** features MIG brazing with and without pulse of galvanised steel plates.

This function ensures maintenance of the materials in terms of corrosion and strength and reduces to a minimum post-treatment of distortion of plates and profiles. The result is cost-effective and efficient welding.

OUR WELDING EXPERTISE

FOCUSED ON YOUR RESULTS

PERFECT FOR JOINING SHEET METALS AND BUILDING UP CAR BODIES.

CMI300 PULSE BRINGS 36 PRE-SET PROGRAMS

The programs meet the requirements for welding and brazing for example high-tensile steel and aluminium, which are used by the auto business.

DOUBLE PULSE FOR WELDING AND BRAZING

CMI300 Pulse features double pulse – a function required by several OEMs.

BOOST FOR ALL MAINS MAINS VOLTAGES

The **CMI300 Pulse** is available with a built-in Boost Converter (electronic auto transformer) for welding on all mono-phase and three-phase mains voltages from 208V to 440V (50/60 Hz).

IGC® - FOR OPTIMAL SHIELDING OF WELD POOL

IGC (Intelligent Gas Control)* ensures optimal shielding of the weld pool and maintains the strength in the joint in the best way possible. The result is large-scale gas savings and a minimum of weld spatter.

MIG-A TWIST®

The ergonomic **MIG-A Twist** torch has a turnable swan neck for easy access to hard-do-reach locations.

MIG-A Twist is available in different lengths and with different swan necks. It is configurable with different control units for adjustment of welding current at the torch handle. The control unit is easy to exchange as required without the use of tools.

FEATURES AND BENEFITS

- **DOUBLE PULSE** ensures precise control of the arc and minimises weld spatter
- FOUR-ROLL WIRE SYSTEM for stable wire feeding
- TACHO CONTROL of wire motor for ultra precise feeding
- LED LIGHT in the wire console for easy change of wire and wire rolls in low-light environment
- SOFT-KEY CONTROL PANEL with colour display and an intuitive icon-based menu
- ARC ADJUST function for precision adjustment between soft and hard arc
- SOFTWARE UPDATE via SD card
- LOG FOR STORAGE and display of welding data on an SD card, applicable for documentation of compliance with repair procedures*



*Available as optional feature



PRODUCT INFORMATION

AND TECHNICAL DATA

ALL OUR WELDING EXPERTISE FOCUSED ON YOUR RESULTS



SPECIFICATION	CMI300 PULSE SINGLE	CMI300 PULSE DUO	CMI300 PULSE TRIO
Current range, A	15 - 300	15 - 300	15 - 300
Mains voltage +/÷ 15%, (50-60Hz) V	3x400	3x400	3x400
Minimum generator size, kVA	16	16	16
Duty cycle 100% /40°, A / V	200 / 100 / 24.0	200 / 100 / 24.0	200 / 100 / 24.0
Duty cycle 100% /40°, A / V	230 / 60 / 25.5	230 / 60 / 25.5	230 / 60 / 25.5
Duty cycle max. /40°, A / % / V	300 / 20 / 29.0	300 / 20 / 29.0	300 / 20 / 29.0
Duty cycle 100% /20°, A / V	250 / 100 / 26.5	250 / 100 / 26.5	250 / 100 / 26.5
Duty cycle max. /20°, A / % / V	300 / 60 / 29.0	300 / 60 / 29.0	300 / 60 / 29.0
Open circle voltage, V	50-60	50-60	50-60
Protection class (for outdoor use)	IP 23S	IP 23S	IP 23S
Norm	IEC60974-1. IEC60974-5. IEC60974-10 Cl. A		
Dimensions (H x W X L)	838x443x1003mm (32.99x17.44x39.48in)	1104x597x1003mm (32.99x17.44x39.48in)	1104x597x1003mm (32.99x17.44x39.48in)
Weight	49kg (108.02lb)	63kg (138.89lb)	67kg (147.71lb)

WE CARE ABOUT BODY SHOPS

EXCELLENCE. INNOVATION. PASSION.

CAR-O-LINER ACADEMY

THE TRAINING









COMPLEXITY

YOU NEED

We enhance our customer's abilities by identifying the real competence and development needed. Offering solutions to meet these needs and accelarate the business growth.

WE OFFER THE SOLUTION







WE FIX THE ROOT OF THE PROBLEMS



WE MEASURE RESULTS

CUSTOMER SUPPORT

The Car-O-Liner Group headquarters is located in Gothenburg, Sweden, with subsidiaries located in Norway, Germany, France, United Kingdon, Italy, China, India, United States, Thailand and Middle East.

Wherever you are, Car-O-Liner can provide customer with product information, training, support or data subscription/renewal.

CHINA:

+86 10 6789 2123 info@car-o-liner.cn

FRANCE:

+33 1 69 52 7750 france@car-o-liner.net

GFRMANY:

+49 (0) 6073 74487-0 info.germany@car-o-liner.se

INDIA:

+91 844 757 0029 info.india@car-o-liner.se

ITALY:

+39 059 468 310 info.carolineritalia@car-o-liner.se

MIDDLE EAST/AFRICA:

+971 6 566 8702 info@caroliner.ae

NORWAY:

+47 3343 0270 info@car-o-liner.no

SWEDEN:

+46 31 721 1050 info@car-o-liner.se

THAIL AND:

+66 2 026 32 55 info.apac@car-o-liner.se

UNITED KINGDON:

+44 1788 574 157 info@car-o-liner.co.uk

UNITED STATES:

1-800 521 9696 info@car-o-liner.com

FIND A DISTRIBUTOR NEAR YOU

Rely on our professional service teams in over 70 countries to define which Car-O-Liner product suits you best. Please visit our website: www.car-o-liner.com

CAR-O-LINER®



CAR-O-LINER®





Car-O-Liner® (2018) is a trademark of Snap-on Incorporated. All rights reserved.

Product images are for illustrative purposes only and may differ from the actual product. Car-O-Liner reserves the right to modify any content without prior notice.