



BENCHRACK™

BENCH EFFICIENCY WITH SCISSOR LIFT VERSATILITY



In-ground installation

FEATURES AND BENEFITS

- **OEM APPROVALS** more equipment approvals, achieved by testing and working closely with major manufacturers worldwide
- **VERSATILE** four length options (14, 16, 18, 21ft) allow you to choose the perfect *BenchRack* for your shop
- **POWERFUL** 10-ton draw aligner pulls from almost any angle, 360° around the vehicle; add a second (optional) for double pulling power
- **FLEXIBLE INSTALLATION** allows in-ground or above ground installation to accommodate all workshop sizes



SPEED™/SPEED™ PLUS

VERSATILITY SPEEDS THINGS UP



FEATURES AND BENEFITS

- **PROFITABLE** increase light-to-medium repairs with quick drive/roll over lifting
- **ERGONOMIC** reach damaged areas easier with no ramps or posts around the vehicle
- **FLEXIBLE** above or in-ground installation
- **STRONG** 5-ton draw aligner with multi-angle pulling capacity

QUICK42™

QUICK BENEFITS FOR YOUR BOTTOM LINE



FEATURES AND BENEFITS

- **POWERFUL** electric hydraulic 10-ton draw aligner pulls from almost any angle, 360° around the vehicle
- **COMPATIBLE** with EVO™ 1, 2 & 3 and the Car-O-Tronic® electronic measuring systems
- **FLEXIBLE INSTALLATION** fixed, mobile or in-ground installation makes it easy to fit into any workshop
- **ACCESSIBLE** drive-on ramps with integrated hydraulic power unit allow for mobility

sssc01BW/21002a_Bench-Selector-US-2p-04.05.2022



OUR PURPOSE:


TO SUPPORT YOUR BUSINESS' GROWTH AND DEVELOPMENT BY DESIGNING EQUIPMENT THAT IMPROVES SERVICE QUALITY, SAFETY, AND PROFITABILITY



SPEED/SPEED™ PLUS



QUICK42™



BENCHRACK™

SEGMENT	Cars and small SUVs	Cars and SUVs	Cars, Trucks, and SUVs			
LIFTING PLATFORM						
LENGTH	8ft 3in	13ft 10in	4200 13ft 10in	5000 16ft 5in	5500 18ft	6300 20ft 8in
WIDTH	2ft 6in (3ft 1in with arms)	3ft 8in	3ft 11in			
MAX. LENGTH (with draw aligner)	11ft 9.5in	17ft 5.5in	Bench length + 3ft 8in			
MAX. WIDTH (with draw aligner)	8ft 2in	7ft 4in	7ft 6.5in			
WIDTH (with ramps attached)	–	6ft 3in	6ft 8in standard ramps 7ft 4in wide ramps			
MIN. HEIGHT	4in	1ft 7in	1ft 4in			
MAX. HEIGHT (floor to top of platform)	5ft 3in	4ft 10in	3ft 11in			
WORK AREA SIZE (with draw aligner)	11ft 9in ²	11ft 8in ²	11ft 2in ²			
TOTAL WEIGHT (lift and work platform)	1371lbs (600kg)	1661lbs (755kg)	2094 - 2866lbs (950 - 1300kg)			
IN-GROUND CAPABILITY	–	YES	YES			
TILT FEATURE	–	YES	YES			
LOADING ANGLE	–	Bench 3.5° Driving ramps 12°	Bench 2.6° Driving ramps 12°			
LIFT CAPACITY (max. vehicle weight)	5500lbs (2500kg)	6600lbs (3000kg)	9259lbs (4200kg)			
HYDRAULICS						
PULLING FORCE (per draw aligner)	5 tons	10 tons	10 tons			
HYDRAULIC PRESSURE (max.)			700 bar			
POWER UNIT						
HYDRAULIC PRESSURE	210 bar	–	210 bar			
AIR CONNECTION PRESSURE	max 10 bar	–	max 10 bar			
SOUND LEVEL	Below 70 dB(A)	–	Below 70 dB(A)			
ELECTRICAL CABLE LENGTH	13ft	–	13ft			
HYDRAULIC HOSE LENGTH	1ft 11in	–	1ft 11in			
CABLE TO CONTROL BOX	32ft 9in	–	32ft 9in			
360° PULLING CAPABILITY	YES	YES	YES			
POWER	Single Phase 60Hz, 110/220V		110 V or 220 V (Single Phase)			



29900 Anthony Drive, Wixom, MI 48393-3609 | Tel: 1 248 624 5900 | 1 800 521 9696 | info@car-o-liner.com

Product images are for illustrative purposes only and may differ from the actual product. Car-O-Liner® reserves the right to modify any content without prior notice. Car-O-Liner® (2022) is a trademark of Snap-on® Incorporated. All rights reserved.

CAR-O-LINER®
car-o-liner.com