

PRODUCTIVITY AND ACCURACY

The CAR-O-LINER® CTP 45^{TM} Two-Post Lift provides versatility and convenience for service and repairs on vehicles up to 4,500 kilograms.

This two-post lift is equipped with Versymmetric technology to combine symmetric and asymmetric lift adjustments into one piece of equipment, bringing flexibility to any service bay and maximizing efficiency and shop space.

The CTP 45[™] ensures the safe lifting of a wide range of vehicles, from passenger cars to light commercial trucks. Versymmetric technology gives you the freedom to service all of these vehicles from the same service bay.

MAXIMUM VERSATILITY VALUABLE PRODUCTIVITY




THREE-STAGE ARMS

Front and rear three-stage arms always allow perfect access to the pick-up points of the vehicle.



CARRIAGE CLEARANCE

The lifting carriage has a rugged design with integrated grease fitting and optimal door clearance with a rubber guard on the carriage to protect the car door.



VERSYMMETRIC® TECHNOLOGY

Combining the advantages of an asymmetric and symmetric lift. Versymmetric Technology improves ergonomics when placing the arms to lift the car.



FLEXIBLE INSTALLATION

The lift is available in two versions for your choice of height: low and high.

ACCESSORIES



PICK-UP PAD EXTENSIONS EAK0339V04A



PICK-UP PAD EXTENSIONS EAK0339V09A



PICK-UP PAD FOR VANS AND LIGHT TRUCKS H6464297

TECHNICAL SPECIFICATIONS

Lifting Capacity	10,000 lbs. 4,500 kg
Configuration	Versymmetric®
Overall Width	142" 360cm
Overall Height	Standard: 156"-169" 395-430cm Extended: 181"-195" 460-495cm
Max Lifting Height	Surface Mount: 77.5" 197cm
Lifting Time	30 seconds
Power Requirements	400-415V 50Hz 3Ph
Minimum Recommended Bay Size WxL	Standard: 11'x19' 335x578cm

OPTIONAL ACCESSORIES

- Secondary Control Box. PROMO until 2023-12-31
- Holder for Pick-Up Pad Adaptors
- Pick-Up Pad Extensions 3" | 7.5cm
- Energy Station Air Supply 1 Phase 230 Volt