CAR-O-LINER® AWARD WINNING TRUP

TRU-POINT ONE-STOP SOLUTION

EASY AND FAST CALIBRATION WITH PROCESS VALIDATION

Tru-Point™ uses highly accurate, advanced camera technology, targets, and top-of-the-line software to quickly uncover any alignment problems a vehicle might have, so you can perform a perfect ADAS calibration.

manual measurements or complicated guide references. Our intuitive,

FLOOR LEVEL IS CRITICAL FOR PROPER CALIBRATION

levelness on the workshop floor. In cases where there is excessive guaranteeing precision even in challenging operational environments.



Steps Required for a Correct Calibration

It takes more than just pushing a few buttons for a precise ADAS calibration. In order to produce accurate and reliable results, shops must take into account a number of essential steps and follow the appropriate procedures.

FLOOR SPACE LIGHTING

ADAS calibrations require open space and proper lighting which our ADAS Specialists can assist you with for successful calibrations.

SERVICE INFORMATION

Any damage to the vehicle may damage sensors and cameras. Access to repair procedures is key for returning vehicles to safe operating conditions.

VEHICLE ALIGNMENT

Cameras and sensors use different inputs from the vehicle to operate properly. Most OEMs require wheel alignment to be performed prior to ADAS calibration.

TARGET PLACEMENT

Accurate target positioning will drive the success of calibration, as well as the shop's productivity and profitability. Most importantly, it needs to follow OEM-specific target placement instructions.

SCAN TOOL

Tru-Point is scan tool agnostic. A comprehensive scan tool with ADAS functionality is all you need to complete calibrations. Tru-Point works with aftermarket, OEM, J2534, or remote calibration services.

Tru-Point™ seamlessly adjusts the height of a target, ensuring it remains in the perfect field of view of the camera while moving equipment in the distance.

- OFM COMPLIANT
- VEHICLE ALIGNMENT CHECK
- PROOF OF TARGET PLACEMENT
- COMPENSATE FOR AN UNIFVEL FLOOR
- NO MANUAL MEASUREMENTS

TRUE FLOOR LEVELING COMPENSATION




Maximum Precision

Achieving the highest level of precision is no longer a challenge. A simple color-coded visual indicator allows you to easily identify the exact location for target placement, going from red to green. Done!









Validation Report

Tru-Point^w generates a printout report as evidence that the targets were placed according to OEM specifications during the procedure. Not only does the printout list and indicate that the ADAS components were placed correctly around the vehicle for all the possible unique measurement properties, but it also confirms that the vehicle's wheel alignment meets the specifications required for calibration.

- **⊘THRUST LINE / CENTRELINE**
- **⊘ DISTANCE FROM VEHICLE**
- **TARGET ROTATION**
- **⊘TARGET POSITION**
- **⊘ TARGET HEIGHT**
- **⊘ RIDE HEIGHT**
- **⊘ WHEEL ALIGNMENT**
- **⊘ STEERING ANGLE**

COMPREHENSIVE COVERAGE TAILORED TO ANY SHOP'S NEEDS

	Included		Premium
×	Vehicle Spec Update	\bigcirc	Vehicle Spec Update
\bigcirc	Front Camera	\bigcirc	Front Camera
\bigcirc	Front Radar Cones	\bigcirc	Front Radar Cones
×	Blind Spot	\bigcirc	Blind Spot
\bigcirc	Front Radar Plates	\bigcirc	Front Radar Plates
×	Park Assist	\bigcirc	Park Assist
×	360° View	\bigcirc	360° View
×	Rear Camera	\bigcirc	Rear Camera
×	Night Vision	\bigcirc	Night Vision
×	Lidar	\bigcirc	Lidar
×	Manual Mode	\bigcirc	Manual Mode



OEM Compliant

Tru-Point™ was specially designed to enhance the productivity of ADAS calibration procedures, and to increase confidence that the process is done in compliance with OEM recommended guidelines.

TRU-PŅINT ONE-STOP SOLUTION

Partners









Certifications







Click or Scan



COVERAGE GUIDE



INSTRUCTIONAL VIDEOS

Tru-Point - Car-0-Liner - EU Nordic Trikog-ust

Tru-Point™

Technical Specifications		
Tyre Size (AC400)	19"-39" 48-99 cm	
	Arms Extended: 82"x113"x30"	
Dimensions (HxWxD)	208x287x76 cm	
Difficilisions (fixfixe)	Arms Folded: 82"x53"x30"	
	208x135x76 cm	
Weight	Equipment: 376 lbs. 171 kg	
Davis Davis and the	Shipping: 512 lbs. I 232 kg 100-240V	
Power Requirements		
Display	24" TFT	
Standard	Optional	
Two Wheel Chock	Target Storage Cart	
AC400 Clamps		
Warranty		
24 months parts and labor		



CAR-O-LINER®

car-o-liner.com